

SOT-23

TABLE 2 – SILICON PLANAR MEDIUM POWER TRANSISTORS

Devices in this table are suitable for medium current, medium power switching and general purpose applications.

Ratings and Characteristics at 25 °C ambient temperature.

Type	— Maximum Ratings —				h _{FE}		V _{CE(max)}		Noise Figure	
	V _{CE(s)} Volts	V _{CE0} Volts	I _C mA	P _{tot} mW	min/max	at I _C /V _{CE} mA/Volts	max Volts	at I _C /I _B mA	f _T at I _C =20 mA MHz(min)	at I _C =0.2mA dB(max)
n-p-n										
BCW65A	60	32	1000	350	100/250	100/1	0.3	100/10	100	10
BCW65B	60	32	1000	350	160/400	100/1	0.3	100/10	100	10
BCW65C	60	32	1000	350	250/630	100/1	0.3	100/10	100	10
BCW66F	75	45	1000	350	100/250	100/1	0.3	100/10	100	10
BCW66G	75	45	1000	350	160/400	100/1	0.3	100/10	100	10
BCW66H	75	45	1000	350	250/630	100/1	0.3	100/10	100	10
BCX19/19R	50	45	1000	310	100/600	100/1	0.62	500/50	200†	—
BCX20/20R	30	25	1000	310	100/600	100/1	0.62	500/50	200†	—
BSS66/66R	60	40	200	200	50/150	10/1	0.20	10/1	250	6†
BSS67/67R	60	40	200	200	100/300	10/1	0.20	10/1	300	5†
p-n-p										
BCW67A	45	32	1000	350	100/250	100/1	0.3	100/10	100	10
BCW67B	45	32	1000	350	160/400	100/1	0.3	100/10	100	10
BCW67C	45	32	1000	350	250/630	100/1	0.3	100/10	100	10
BCW68F	60	45	1000	350	100/250	100/1	0.3	100/10	100	10
BCW68G	60	45	1000	350	160/400	100/1	0.3	100/10	100	10
BCW68H	60	45	1000	350	250/630	100/1	0.3	100/10	100	10
BCX17/17R	50	45	1000	310	100/600	100/1	0.62	500/50	100†	—
BCX18/18R	30	25	1000	310	100/600	100/1	0.62	500/50	100†	—
BSS69/69R	40	40	200	200	50/150	10/1	0.25	10/1	200	5†
BSS70/70R	40	40	200	200	100/300	10/1	0.25	10/1	250	4†

†Typical.