

TO 39
(CB 7)TO 18
(CB 6)TO 92
(CB 97)F 139 B
(CB 76)Silicon PNP transistors, general purpose
Transistors PNP silicium, usage général $T_{amb} = 25\text{ }^{\circ}\text{C}$

Type	Case Boîtier	P_{tot} (mW)	V_{CE0} (V) V_{CEr}^* V_{CEX}^{\square}	h_{21E} h_{21E} min	h_{21E} max	I_C (mA)	V_{CEsat} (V) max	I_C/I_B (mA)	f_T (MHz) min	t_s (ns) t_{off} max	TSi 76 Page
2N 1131	TO 39	600	-35	20	45	-150	-1,5	150/15	50		131
2N 1132	TO 39	600	-35	30	90	-150	-1,5	150/15	50		131
2N 2904	TO 39	600	-40	40	120	-150	-1,5	500/50	200	175	229
2N 2904 A	TO 39	600	-60	40	120	-150	-1,5	500/50	200	175	229
2N 2905	TO 39	600	-40	100	300	-150	-1,5	500/50	200	200	229
2N 2905 A	TO 39	600	-60	100	300	-150	-1,5	500/50	200	200	229
2N 2906	TO 18	400	-40	40	120	-150	-1,6	500/50	200	175	235
2N 2906 A	TO 18	400	-60	40	120	-150	-1,6	500/50	200	175	235
2N 2907	TO 18	400	-40	100	300	-150	-1,6	500/50	200	200	235
2N 2907 A	TO 18	400	-60	100	300	-150	-1,6	500/50	200	200	235
2N 3702	TO 92 \circ	360	-25	60	300	-50	-0,25	50/5	100		#
2N 3703	TO 92 \circ	360	-30	30	150	-50	-0,25	50/5	100		#
2N 3905	TO 92 \circ	350	-40	50	150	-10	-0,4	50/5	200	200	#
2N 3906	TO 92 \circ	350	-40	100	300	-10	-0,4	50/5	250	225	#
2N 4058	TO 92 \circ	360	-30	100	400	-0,1	-0,7	10/0,5			#
2N 4059	TO 92 \circ	360	-30	45	660	-1	-0,7	10/0,5			#
2N 4060	TO 92 \circ	360	-30	45	165	-1	-0,7	10/0,5			#
2N 4061	TO 92 \circ	360	-30	90	330	-1	-0,7	10/0,5			#
2N 4062	TO 92 \circ	360	-30	180	660	-1	-0,7	10/0,5			#
2N 4125	TO 92 \circ	350	-30	50	150	-2	-0,4	50/5	200		#
2N 4126	TO 92 \circ	350	-25	120	360	-2	-0,4	50/5	250		#
2N 5365	TO 92 \circ	360	-40	40	120	-50	-1	300/30	250§		289
2N 5366	TO 92 \circ	360	-40	100	300	-50	-1	300/30	250§		289
*2N 5447	F 139 B \circ	360	-25	60	300	-50	-0,25	50/5	100		293
*2N 5448	F 139 B \circ	360	-30	30	150	-50	-0,25	50/5	100		293
BC 160	TO 39	650	-40	40	250	-100	-1	1000/100	50		313
BC 161	TO 39	650	-60	40	250	-100	-1	1000/100	50		313
BC 177 VI	TO 18	300	-45	75	150*	-2	-0,95	100/5	200§		319
BC 177 A	TO 18	300	-45	125	260*	-2	-0,95	100/5	200§		319
BC 178 VI	TO 18	300	-25	75	150*	-2	-0,95	100/5	200§		319
BC 178 A	TO 18	300	-25	125	260*	-2	-0,95	100/5	200§		319
BC 178 B	TO 18	300	-25	240	500*	-2	-0,95	100/5	200§		319
BC 179 A	TO 18	300	-20	125*	260*	-2	-0,95	100/5	200§		319
BC 179 B	TO 18	300	-20	240*	500*	-2	-0,95	100/5	200§		319
*BC 212	F 139 B \circ	300	-50	60	300	-2	-0,6	100/5	200		347

* Preferred device § Typical value \circ Plastic case # To be published later
Dispositif recommandé Valeur typique Boîtier plastique Sera publiée ultérieurement