



M/A-COM

ISO 9001
CERTIFIED

E-Series RF 4:1 Transformer 1.5 - 600 MHz

ETC4-1T-3

Features

- * 4:1 Impedance Ratio
- * CT on Secondary

Specifications @ 25°C


Frequency Range	1.5 - 600 MHz
-----------------	---------------

Insertion Loss	Maximum
1.5 - 600 MHz	3 dB
7 - 450 MHz	2 dB


Amplitude Imbalance	Maximum
1.5 - 100 MHz	0.2 dB
1.5 - 600 MHz	1 dB

Phase Imbalance	Maximum
1.5 - 100 MHz	2°
1.5 - 600 MHz	10°

Schematic



SM-22



Absolute Maximum Ratings

Parameter	Absolute Maximum
RF Power	250 mW
DC Current	30 mA
Operating Temperature	-20°C to +85°C
Storage Temperature	-55°C to 100°C

Function	Pin No.
Primary dot	5
Primary	4
Primary CT	-
Secondary dot	1
Secondary	3
Secondary CT	2
Case Ground	-
Not Connected	-

Specifications Subject to Change Without Notice

S 0636 D

AMP M/A-COM Eurotec * Loughmahon Technology Park * Blackrock * Cork * Ireland * Tel: 353-21-808300 * Fax: 353-21-359935

www.datasheet.technology