

MILITARY TYPES AVAILABLE

Type	TX Type	Military Specification
JAN 1N93A		MIL-S-19500/293
JAN 1N249B, 250B		MIL-S-19500/134
JAN 1N1184, 6, 8	JANTX 1N1184, 6, 8	MIL-S-19500/297
JAN 1N1202A, 04A	JANTX 1N1202A, 04A	MIL-S-19500/260
JAN 1N1206A	JANTX 1N1206A	MIL-S-19500/260
JAN 1N1614, 15, 16		MIL-S-19500/162
JAN 1N2135A		MIL-S-19500/134
JAN 1N3289, 91, 93, 94, 95		MIL-S-19500/246
JAN 1N3713, 15, 17, 19, 21		MIL-S-19500/269
JAN 1N3880, 81, 83		MIL-S-19500/266
JAN 1N3890, 91, 93	JANTX 1N3890, 91, 93	MIL-S-19500/304
JAN 1N3909, 10, 11, 12, 13		MIL-S-19500/308
JAN 1N4148	JANTX 1N4148	MIL-S-19500/116
JAN 1N4150	JANTX 1N4150	MIL-S-19500/231
JAN 1N4153	JANTX 1N4153	MIL-S-19500/337
JAN 1N4245		MIL-S-19500/286
JAN 1N4246, 7, 8		MIL-S-19500/286
JAN 1N4454	JANTX 1N4454	MIL-S-19500/144
JAN 1N4531	JANTX 1N4531	MIL-S-19500/116
JAN 1N4532		MIL-S-19500/144
JAN 2N43A, 44A		MIL-S-19500/6

Type	TX Type	Military Specification
JAN 2N78A		MIL-S-19500/90
JAN 2N167A		MIL-S-19500/11
JAN 2N396A		MIL-S-19500/64
JAN 2N461		MIL-S-19500/45
JAN 2N489A-94A	JANTX 2N489A-94A	MIL-S-19500/75
JAN 2N526		MIL-S-19500/60
JAN 2N682, 3, 5, 6, 7, 8, 9		MIL-S-19500/108
JAN 2N1303, 5		MIL-S-19500/126
JAN 2N1307		MIL-S-19500/126
JAN 2N1771A, 2A, 4A, 6A, 7A	JANTX 2N1771A, 2A, 4A, 6A, 7A	MIL-S-19500/168
JAN 2N1792, 3, 5, 7, 8		MIL-S-19500/204
JAN 2N1910, 11, 13, 15, 16		MIL-S-19500/204
JAN 2N2031		MIL-S-19500/204
JAN 2N2060	JANTX 2N2060	MIL-S-19500/270
JAN 2N2323, 24, 26 & A	JANTX 2N2323, 24, 26 & A	MIL-S-19500/276

Datasheet.Technology

HIGH RELIABILITY SPECIFICATIONS

High Rel. Type	Commercial Type	Conservative Design Maximum Conditions				Estimated Maximum Failure Rate in Conservatively Designed Equipment %/1000 hrs.
		I _O	T _{STG} , T _{JOP}	V _{DRM} , V _{RRM}	V _{RSM}	
A27BR1200	1N1202	12A	-65 to +100°C	100V	200V	.001
A27DR1200	1N1204	12A	-65 to +100°C	200V	400V	.001
A27MR1200	1N1206	12A	-65 to +100°C	400V	600V	.001
A28BR1200	A28B	12A	-65 to +100°C	100V	200V	.001
A28DR1200	A28D	12A	-65 to +100°C	200V	400V	.001
A28BR1201	1N3891	12A	-65 to +100°C	100V	200V	.001
A28DR1201	1N3893	12A	-65 to +100°C	200V	400V	.001
A38BR1200	1N2156	25A	-65 to +100°C	100V	200V	.001
A38DR1200	1N2158	25A	-65 to +100°C	200V	400V	.001
A38MR1200	1N2160	25A	-65 to +100°C	400V	600V	.001
A38BR1202	1N3911	30A	-65 to +100°C	100V	200V	.001
A38DR1202	1N3913	30A	-65 to +100°C	200V	400V	.001

continued on next page